



Instructions for proper cargo securing

Purpose of the instructions

The purpose of the instructions is to prevent cargo damage during transport.

If the cargo is not secured in accordance with the instructions below, any claims due to during transport damaged cargo will be rejected.

- Before loading the truck, make sure that the straps are placed in a way that they do not interfere the loading.



PICTURE 1: Correct placement of the straps before the loading.

- Before loading the cargo, **anti-slip rubber** must be applied to each side of the pallet along the entire length that is loaded.



PICTURE 2: Placing the anti-slip rubber.



PICTURE 3 and 4: Placing the anti-slip rubber.

- The cargo security straps must be fastened over the top and bottom pallets. Two stacked pallets must be secured with **at least three safety straps**, with one strap binding the lower pallet and the other two binding the lower and upper pallet. Plastic corners must be placed under the straps to protect the load from pressure.



PICTURE 5: Demonstration of proper fastening of cargo security straps (indicated in green).



PICTURE 6: Demonstration of the correct installation of cargo security straps and plastic corners.

- If the truck or the trailer is not filled completely, it is necessary to prevent the load from moving longitudinally. This must be done with a double intermediate block bar, which holds the top and bottom pallets.



PICTURE 7: Demonstration of using a double intermediate block bar.

Official Working Hours:

Monday to Friday, 8.00 – 14.30

Loading Address:

Latkova vas 59a, 3312 Prebold, Slovenia